


# Easy Universal Sway Brace



## Features

- Use for both lateral and longitudinal sway brace applications
- Unique slotted holes provide for easy slip-on installation eliminating loose hardware
- Snap-off bolt head helps enable easy installation and inspection of seismic sway braces
- Works with 1" through 2" brace pipes and 1/4" angle iron braces to reduce inventory
- Meets NFPA®-13 requirements for seismic sway bracing



## Specifications

Material: Steel  
Finish: Electro-galvanized



Part Number	Pipe Size	A	B	Listings Approvals
CSBEZU0100EG	1"	6 7/8"	1"	UL, FM
CSBEZU0125EG	1 1/4"	7 3/8"	1"	UL, FM
CSBEZU0150EG	1 1/2"	7 3/4"	1"	UL, FM
CSBEZU0200EG	2"	8 1/8"	1 3/16"	UL, FM
CSBEZU0250EG	2 1/2"	8 7/8"	1 3/16"	cUL, UL, FM
CSBEZU0300EG	3"	9 3/8"	1 3/16"	cUL, UL, FM
CSBEZU0400EG	4"	10 5/8"	1 1/2"	cUL, UL, FM
CSBEZU0500EG	5"	12 1/8"	1 1/2"	cUL, UL, FM
CSBEZU0600EG	6"	13 5/8"	2"	cUL, UL, FM

DISTRIBUIDOR AUTORIZADO MEXICO WWW.SPROFIRE.COM  
ventas@sprofire.com

